

jc813 U.S. PTO
06/07/00

06-08-00

Please type a plus sign (+) inside this box →

+

PTO/SB/05 (12/97)
Approved for use through 09/03/00 OMB 0651-0032





+

Patent and Trademark Office: U. S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>	Attorney Docket No.	10717RNUS01U	Total Pages	58
	First Named Inventor or Application Identifier			
	Kahveci, T.			
	Express Mail Label No.	EL355509825US		

jc571 U.S. PTO
09/589414
06/07/00

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231																										
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form <small>(Submit an original, and a duplicate for fee processing)</small></p> <p>2. <input checked="" type="checkbox"/> Specification [Total Pages 44] <small>(preferred arrangement set forth below)</small></p> <ul style="list-style-type: none">- Descriptive title of the Invention- Cross References to Related Applications- Statement Regarding Fed sponsored R & D- Reference to Microfiche Appendix- Background of the Invention- Brief Summary of the Invention- Brief Description of the Drawings <i>(if filed)</i>- Detailed Description- Claim(s)- Abstract of the Disclosure <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets 8]</p> <p>4. Oath or Declaration [Total Pages 3]</p> <ul style="list-style-type: none">a. <input type="checkbox"/> Newly executed (original or copy)b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) <small>(for continuation/divisional with Box 17 completed)</small>i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting Inventor(s) named in the prior application, see 37 CFR 1.63(d) and 1.33 (b). <p>5. <input type="checkbox"/> Incorporation By Reference <small>(usable if Box 4b is checked)</small> The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being a part of the disclosure of the accompanying application and is hereby incorporated by reference therein.</p>	<p>6. <input type="checkbox"/> Microfiche Computer Program <i>(Appendix)</i></p> <p>7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission <i>(if applicable, all necessary)</i></p> <ul style="list-style-type: none">a. <input type="checkbox"/> Computer Readable Copyb. <input type="checkbox"/> Paper Copy (identical to computer copy)c. <input type="checkbox"/> Statement verifying identity of above copies <p>ACCOMPANYING APPLICATION PARTS</p> <p>8. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))</p> <p>9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input type="checkbox"/> Power of Attorney <i>(when there is an assignee)</i></p> <p>10. <input type="checkbox"/> English Translation Document <i>(if applicable)</i></p> <p>11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations</p> <p>12. <input type="checkbox"/> Preliminary Amendment</p> <p>13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEM 503) <i>(Should be specifically itemized)</i></p> <p>14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, Status still proper and desired</p> <p>15. <input type="checkbox"/> Certified Copy of Priority Document(s) <i>(if foreign Priority is claimed)</i></p> <p>16. <input type="checkbox"/> Other: _____</p>																										
<p>17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:</p> <p><input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No: ___/___</p>																											
<p>18. CORRESPONDENCE ADDRESS</p> <p><input checked="" type="checkbox"/> Customer Number or Bar Code Label  or <input type="checkbox"/> Correspondence address below</p> <table border="1"><tr><td colspan="2">NAME</td></tr><tr><td colspan="2">ADDRESS</td></tr><tr><td>CITY</td><td>STATE</td></tr><tr><td>COUNTRY</td><td>ZIP CODE</td></tr><tr><td>U. S. A.</td><td>TELEPHONE</td></tr><tr><td>FAX</td><td></td></tr><tr><td colspan="2">SUBMITTED BY</td></tr><tr><td colspan="2">Complete (if applicable)</td></tr><tr><td>Typed or Printed Name</td><td>J. Erik Fako</td></tr><tr><td>Reg. No.</td><td>42,522</td></tr><tr><td>Signature</td><td>Date</td></tr><tr><td></td><td>6/7/00</td></tr><tr><td>Deposit Account</td><td>User ID</td></tr></table>		NAME		ADDRESS		CITY	STATE	COUNTRY	ZIP CODE	U. S. A.	TELEPHONE	FAX		SUBMITTED BY		Complete (if applicable)		Typed or Printed Name	J. Erik Fako	Reg. No.	42,522	Signature	Date		6/7/00	Deposit Account	User ID
NAME																											
ADDRESS																											
CITY	STATE																										
COUNTRY	ZIP CODE																										
U. S. A.	TELEPHONE																										
FAX																											
SUBMITTED BY																											
Complete (if applicable)																											
Typed or Printed Name	J. Erik Fako																										
Reg. No.	42,522																										
Signature	Date																										
	6/7/00																										
Deposit Account	User ID																										

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of Time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

06/07/00
JCE13 U.S. PRO



4006 E. Highway 54
Network Center 2, MS D16/02/0E2
Durham, North Carolina 27713
Tel 919.997.4453
Fax 919.997.6659
efako@nortelnetworks.com

www.nortelnetworks.com

J. Erik Fako
Senior Counsel

June 7, 2000

Box Patent Application
Assistant Commissioner
for Patents
Washington, D.C. 20231-9999

Re: U. S. Patent Application
Docket No. 10717RNUS01U
Entitled : A Computer System for Managing Data Exchanges Among
a Plurality of Network Nodes

Dear Sir:

Enclosed is a patent application including formal papers as follows:

Applicant: Tunc M. Kahveci, et al.

Title : A Computer System for Managing Data Exchanges Among a Plurality
of Network Nodes

No. Pages Specification: 30; Claims: 13; Abstract: 1; Informal Drawings: 8;
Unexecuted Power of Attorney

Kindly acknowledge receipt of the foregoing by returning the enclosed self-
addressed postcard.

Sincerely,

A handwritten signature in black ink, appearing to read "Erik Fako", written over a horizontal line.

Erik Fako

JEF:sfp
EL355509825US

CERTIFICATE OF EXPRESS MAILING

EXPRESS MAILING LABEL NO. EL355509825US
DATE OF DEPOSIT: 6/7/00



I hereby certify that the accompanying application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, DC 20231.

Sharon F. Preston

Name: Sharon F. Preston

Date of Signature: 6/7/00

TITLE OF THE INVENTION

A Computer System For Managing Data Exchanges
Among A Plurality Of Network Nodes

5

FIELD OF THE INVENTION

The present invention relates generally to a method
and apparatus for delivering and metering high bandwidth
multi-media content and services from Application Service
Providers to subscribers utilizing a managed packet
10 backbone network.

BACKGROUND OF THE INVENTION

Several market dynamics have come together recently to
create an environment for significant change in the
15 computer and telecommunication industries. Explosive
growth of the Internet has led to changes in the way
regional telephone companies (telcos) view their networks.
The Telecommunications Act of 1996 spawned an environment
where entrepreneurs can capitalize on niche openings, and
20 large corporations (e.g. Public Utilities) find themselves
in position to offer new revenue generating services.
Technical advances in personal computers and network router
technology have created an environment where next
generation multimedia applications are ready to skyrocket.
25 Recent corporate mergers have brought the cable industry to
the forefront of the telecommunications market while other
mergers and new market entrants have shown that the long
haul backbone is moving to packet based technology.

These changes taken independently result in
30 interesting evolutionary steps that can be implemented
within the framework of existing product platforms and

processes. Taken as a whole, however, they beckon a revolution - a new class of telecommunications products and a new network paradigm.

5 Until the late 1970's analog techniques were used in the Public Switched Telephone Network (PSTN). The Customer Premise Equipment (CPE), a residential phone or private branch exchange, were analog and the circuits connecting the CPE to a telco central office were analog. Analog techniques were used to switch telephone calls within the
10 central office as well as between central offices.

 Digital switches and ISDN introduced techniques for converting analog speech to digital bit streams. The conversion was standardized. Digital techniques supplanted analog and were used to switch telephone calls within a
15 central office as well as between central offices.

 At the sending end, the analog to digital conversion standard requires sampling the analog signal every 125 microseconds and coding the sample into an eight-bit number that represents the analog amplitude. The sampling and
20 coding follow recommendation G.711. The coded eight bit numbers are placed in 64 KBPS channels. For analog circuits coding occurs in the interface card at the central office and for ISDN lines coding occurs at the CPE. This function is often referred to as a Code/Decode or CODEC function.

25 The G.711 recommendation specifies 64 KBPS per conversation, which for standard human conversations is overkill. The average human conversation requires as little as 4 KBPS to transmit all audible communications using other CODEC technologies. Several other CODECs have been
30 developed including G.722, G.723.1, G.728, G.729, or the

GSM coding standard G.729a, often used in IP telephony. Some of these recommendations were developed to help deal with situations where not as much bandwidth was available to carry the voice conversation which is the case in analog
5 and digital cellular environments.

A PSTN digital telco central office receives 64 KBPS calls from TDM circuits (or converts analog circuits to 64 KBPS) and switches each 64 KBPS channel toward a terminating user. If the local central office serves the
10 terminating user, the channel is sent to the local line circuit. If a distant central office serves the terminating user, digital trunks carry the 64 KBPS information transparently to the central office that services the user.

At the receiving end, the digital to analog conversion
15 standard requires that the 64 KBPS channel information be used to reconstruct an analog signal following the G.711 recommendation. The CODEC used (e.g., G.711) at the sending end dictates what CODEC to use at the receiving end. The same standard must be used to decode the 64 KBPS
20 (or other rate) signal as was used to encode it.

During call establishment, bandwidth is reserved from end to end. All of the network components in the call path reserve bandwidth based on which CODEC is in use, and the network components are all synchronized. Network components
25 include the analog to digital converters (CODECs), digital switches, and digital trunks.

Voice packet switching (e.g., IP telephony) is quite different. Historically, packet switching did not reserve bandwidth between end users nor were packets switched based
30 upon packet priority. Standards work in this area is

ongoing and these capabilities do exist for some network types.

At the sending end, one method for analog to packet conversion is described by H.245. H.245 permits a call to be handled using G.711, G.722, G.723.1, G.728, G.729, or GSM coding standard. When multiple coding standards are supported by the endpoints, H.323 provides a protocol to resolve which coding standard will be used for any specific call.

A local area network receives packets from connected endpoints or gateways. These packets are routed toward a terminating endpoint or gateway. If the terminating address is not on the same local area network, the packet may be routed via a number of routers, switches, connecting trunks, etc.

At the receiving end, packet to analog conversion is required. The receiving end must use the same conversion standard that was used at the sending end. During call establishment, bandwidth may or may not be reserved from end to end. Network components (hubs, routers, switches, etc.) may or may not implement priority-based packet switching. Thus, there is no guarantee of the end to end packet delay. Voice packets may arrive at the receiving end with different inter-packet arrival times and occasionally out of sequence.

Although each subscriber in the PSTN may appear to have dedicated bandwidth, there are concentration points within the network. Sophisticated engineering algorithms have been developed to help network planners determine where in the network to locate concentration points and

what the concentration factors should be. The *Erlang* is a unit of measurement that describes the utilization of TDM circuits within the PSTN. One Erlang is equivalent to one TDM circuit in use 100% of the time.

5 Prior to the popular past time of dialing into your local Internet Service Provider (ISP), PSTN engineering rules assumed that the average residential subscriber received or placed 2 phone calls per hour and each call lasted an average of 3 minutes. This yielded an average
10 Erlangs per subscriber line of 0.1. Of the 0.1 Erlangs, 10% were assumed to be originated or terminated outside of the subscriber's central office. In practical terms, this means that (in general) for every 10 Erlangs of subscriber line use, 1 Erlang of trunking capacity to other central
15 offices is required.

 With the proliferation of Internet service providers (ISPs), this relationship changed drastically. During the evening hours when Internet use is heavy, a much higher percentage of subscriber traffic leaves the subscribers
20 central office. This change caused telcos to look for alternate means of providing data access to subscribers.

 One means at the Local Exchange Carrier's (LEC) disposal is to use a technology known generically as Digital Subscriber Loop or (xDSL). This technology allows
25 analog voice signals to coexist with digital data signals. Subscribers can be directly connected to a data network over their existing twisted pair without interrupting their ability to place phone calls on that same pair. The LEC could then groom the data traffic off the network at the
30 line access point and eliminate the high demand for inter

office trunks. In addition, this opened a new revenue stream for LECs by giving them incentive to become ISPs. The deployment of xDSL has been slow, however, and other high speed Internet access methods are on the horizon.

5 The 1996 Telecommunications Act ushered (or more accurately "is ushering") in a new era of competition in the local service market. A new breed of communications company has been created known as Competitive Local Exchange Carriers or CLECs. Many of the initial CLECs have
10 built their business around offering local service exclusively to the lucrative enterprise business market. The residential market has continued to be monopolized by the LEC.

15 Regulations bodies have been slow to force LECs to open their local loops at reasonable prices and it's impractical for most CLECs to consider building out a residential network.

20 Other access means for the "last mile" to the subscriber residence have been slow to develop. Wireless companies are constrained by available RF bandwidth. Cable operators have just recently been pushing data modems into their cable offerings and had considered the "lifeline" telephony service too large a hurdle to overcome.

25 Initially, cable modems were created to help bring high-speed data access to subscribers that were stuck with 28.8 KBPS modem access. Some ventures have had moderate success, as cable data services have been slow to deploy. Problems with the agreement on standards as well as with old cable plants that did not support 2-way communication
30 made progress slow.

Today, coaxial cable passes 98% of the homes in the United States. 60% of U.S. households subscribe to cable services. In addition, Coaxial Cable Modem standards (known as DOCSIS) currently can provide 2 to 3 times the bandwidth of ADSL technology and are being deployed more quickly.

As competition in the local markets begins to heat up, and with LECs wanting to get into the long distance business, LECs and Inter Exchange Carriers have been consolidating and merging to remain strong. Most Network Access Provider mergers seem to be driven by competition. Traditional telecommunications vendors have been merging with traditional data network vendors to create "Unified Networks" vendors that can deliver both circuit and packet switched networks. Competition and convergence are the two forces driving change in the telecommunications and data communications industries. These two forces often tend to be cumulative in their impact on both traditional Network Access Providers and traditional network infrastructure vendors.

The foregoing illustrates a brief evolution of circuit switched voice and packet switched voice and data services as provided to residential and business subscribers. It is evident that most of the intelligence of these systems is centralized.

SUMMARY OF THE INVENTION

A Residential Access Node (RAN) according to the present invention gives Network Access Providers and Application Service Providers with the ability to deliver multimedia services to subscribers while maintaining

control and security over the bandwidth and content delivered.

A RAN is similar to existing cable interface units in that it is mounted outside of a subscriber's home in a weatherproof enclosure and can accommodate coaxial cable, xDSL, or fiber optic cable among others as it's network interface. It is different from existing cable interface units, however, in that it includes a processor, memory and storage, supplies RJ11 analog telephony interfaces and 10/100BaseT Ethernet interfaces in addition to coaxial cable for broadband network and broadcast TV to the customer premises. RAN communicates with a subsystem in the Network Access Provider headend using a protocol specifically defined for RANs. RAN provides value added services without using the service provider's computer resources. Services include room to room calling within the home, always on access to the Internet, virtual private networking support, and usage based metering. RAN also provides industry standard Application Programming Interfaces (APIs) and protocols to support third party development of applications.

RAN's represent a new class of network interface, and a new way of looking at the customer premises. Currently telecommunications and data communications customers (and to some extent cable subscribers) are broadly classified as either "residential" or "business" subscribers. This classification often refers to whether or not the customer premises equipment is to be treated as a device (residential), or as a network (business).

Many products are coming onto the market that allow residential subscribers to create data networks in their homes, but leave the interface to the network unchanged. This makes delivery of services to "residential private networks" clumsy at best.

RAN's provide Network Access Providers with a platform, protocol, and software environment upon which advanced multimedia services can be delivered and metered.

In accordance with a first embodiment of the invention is a residential access node (RAN) running a RAN platform. The RAN platform includes means for interfacing a plurality of peripheral equipment to a packet data network. Each piece of peripheral equipment, however, does not necessarily operate on the same data type. The RAN platform manages exchanges of data packets with other residential access nodes resident on the packet data network. The RAN platform also determines the number and type of data packets entering or departing from a residential access node via the packet data network.

Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE FIGURES

FIGURE 1 illustrates an environment in which RANs operate.

FIGURE 2 illustrates a diagram of a RAN hardware platform.

FIGURE 3 is a prior art illustration of OSI stack layers.

FIGURE 4 is an illustration of OSI stack layers as applied to one embodiment of the present invention.

5 **FIGURE 5** is an illustration of a session in which RAN protocol data and content data are being exchanged among a Customer Premises RAN platform, a managed packet backbone server (MPBS) RAN platform, and an Application Service Provider (ASP) RAN platform.

10 **FIGURE 6A** illustrates a RAN registration process.

FIGURE 6B illustrates a RAN to RAN session establishment process.

FIGURE 6C illustrates a RAN to RAN session.

FIGURE 6D illustrates a RAN reporting session.

15 DETAILED DISCLOSURE OF THE INVENTION

 No element, step, or instruction used in the description of the present application should be construed as critical or essential unless explicitly described as such.

20 A Residential Access Node (RAN) is comprised of four basic components. First is a hardware platform for high bandwidth access to an Access Network. Second is a Protocol for communication between the Access Network and
25 the customer (subscriber) premises. Third is a software platform for the delivery of services "at the edge" thereby providing the means for traditional telecommunications networks service providers to distribute capabilities into the home. Fourth is a distributed application environment

that can be exploited by a Network Access Provider (NAP) as well as an Application Service Provider (ASP).

A RAN is analogous to the client in a client / server model. A Network Access Provider can implement intelligent packet metering algorithms that support differentiation of IP packets based on their respective content. An Application Service Provider can implement intelligent clients that provide new levels of multimedia inter-activity.

The RAN hardware platform provides three basic functions which include a network interface, an application processing engine, and storage capability. The RAN hardware platform network interface provides a means for interfacing existing or newly developed Customer Premises Equipment (CPE) to the Access Network.

A RAN also provides a broadband network interface (Coaxial Cable) as well as standard coaxial cable, RJ11, and various Ethernet interfaces. In addition to the Access Network and customer premises interfaces, the RAN hardware platform provides a flexible and scaleable application-processing environment. A RAN implements a protocol as well a suite of services and scales from a minimal, low cost implementation to an environment that rivals today's most sophisticated digital switches. A RAN makes use of industry standard CPU hardware to ensure future benefit from "Moore's Law".

The RAN hardware platform further provides the ability to store and retrieve persistent and semi-persistent data at the customer premises. Unlike it's semi-intelligent predecessors, the cable box or ISDN telephone, the RAN

hardware platform provides more rewriteable space in which to store it's base software load and application software as well as data collected during operation.

One RAN Platform may reside at the customer premises.

5 In order to provision and maintain it, this Customer
Premises RAN platform requires a means to establish
communications with the Access Network or, more
specifically, a Network Access Provider RAN platform. This
is accomplished by means of a defined RAN protocol. The
10 RAN Protocol serves three main purposes. One is to provide
a mechanism for Registration, Authentication and Security
(RAS) of the connection from the CPE to the Access Network.
Another is to provide a mechanism for the delivery of and
billing for services. A third is to provide a mechanism
15 for route discovery and advertisement.

As stated above, a RAN includes an interface to the
Access Network for all services provided. As such, there is
a need to ensure that services are delivered only to
authorized subscribers. Further, the delivery of these
20 services should be done in a secure manner so as to protect
the privacy of the subscriber, the Network Access Provider,
and Application Services Providers. Security should also
provide a means for preventing fraudulent use of network
facilities.

25 A RAN implements a protocol for establishing
communications with the Access Network. This protocol
includes a mechanism by which each RAN identifies itself to
the Access Network and requests service by a mechanism in
which each RAN identifies its service capabilities, such as
30 max/min bandwidth requirements, subscriber features

supported, network interfaces supported, applications in residence on the RAN, available network routes, subscriber addresses/aliases supported, and a means by which user profile information is downloaded from the Network Access
5 Provider.

A RAN also implements a protocol for authenticating subscriber access. This protocol includes a software means by which the Network Access Provider grants or denies access to each individual RAN, a software means by which
10 the Network Access Provider grants or denies services on a per use basis, and a software means by which Application Service Providers grant or deny services on a per use and/or user basis without intervention of the Network Access Provider.

A RAN implements a protocol for providing secure access to the Access Network. This protocol includes a means by which the network and a Customer Premises RAN can pass raw data and application specific data securely over the Access Network, and a means by which RANs can pass
20 application specific data to other RANs securely over the Access Network.

Delivery of services to subscribers is the basis for existence of all of the rest of the network capabilities. Billing for these services (either directly or indirectly)
25 is what makes it worthwhile. A RAN implements a protocol that enables the delivery and subsequent billing for services. This protocol includes a means by which packet metering (billing) for raw data flows can be established and reported back to the Network Access Provider RAN
30 platform, a means by which packet metering (billing) for

data flows based on other parameters, such as time of day, content, or day of week, can be established and reported back to the Network Access Provider RAN platform, a means by which the above capabilities can be delivered between an Application Service Provider and a RAN subscriber without the intervention of the Network Access Provider, and a means by which the Network Access Provider can offer the above services to an Application Service Provider without the intervention of the subscriber.

As services migrate from the Access Network to the Customer Premises Equipment (CPE), more and more switching and routing functions will also migrate. A RAN will then require a means to maintain its view of neighboring networks and links. RAN route discovery and advertisement are patterned after the processes currently defined by the ATM Forum entitled Public Network to Network Interface (PNNI). These capabilities allow a RAN to independently switch/route data between itself and other RANs in the network. This capability will enhance RAN's ability to establish and maintain Virtual Private Networks as well as to provide more enhanced services at the network edge.

As was outlined above, RAN is intended to run on more than one hardware platform. To facilitate this, the software is independent from the hardware platform and operating system. A RAN maintains an abstraction layer for those services required from the operating system. To support these activities the RAN implements software application programming interfaces such as TAPI, TSAPI, MAPI, and CSTA. In addition, the RAN platform serves as a residential gateway into a packet telephony based network.

To support this type of interface, H.323, MGCP, SIP, Q.931, MEGACO and DOCSIS protocols can be implemented.

A RAN opens the door to distributing services to residential and small business customers by providing a universal platform. Applications like those found on a traditional PBX are easily integrated onto the RAN platform. Services typically provided by the Network Access Provider can now reside on the RAN platform easing the computing load required of the network.

FIGURE 1 illustrates a typical RAN environment. For purposes of illustration, only one Customer Premises RAN platform and one Application Service Provider RAN platform are shown. The network, however, can support multiple Customer Premises and Application Service Provider RAN platforms.

At the center of this RAN based network architecture is a managed packet backbone **100** which may be owned and operated, for example, by a Network Access Provider (NAP). Managed packet backbone **100** is the communication link among several other networks and entities. For instance, managed packet backbone **100** can connect to the public switched telephone network (PSTN) **102** via a gateway **104**. Managed packet backbone **100** can also connect to the Internet **106** via an Internet service provider (ISP) **108**. The real advantage of this RAN based network, however, is its high bandwidth connection between Application Service Provider RAN platform **110** and Customer Premises RAN platform **112** via managed packet backbone **100**.

Customer Premises RAN platform **112** can physically reside at the customer or subscriber premises and connects

to all of the customer premises equipment (CPE) such as analog telephone(s) **114**, standard television(s) **116**, computer(s) **118**, IP telephone(s) **120**, and high definition television(s) (HDTV) **122**.

5 Application Service Provider (ASP) is an entity that offers services and content over a network directly to a subscriber or network participant. To be of any value to a subscriber, content must be "downloadable" at high data rates. As such, broadband network connections (i.e., those
10 capable of high multi-media data throughput) are utilized end to end between Customer Premises RAN platform **112** and Application Service Provider RAN platform **110**. The Network Access Provider maintains managed packet backbone **100** with the assistance of a managed packet backbone server (MPBS)
15 **124**.

FIGURE 2 illustrates a diagram of a typical RAN hardware platform. Since a RAN is capable of receiving and distributing many different multi-media signals it possesses a hardware platform capable of receiving and
20 distributing the various multi-media signals. At the heart of a RAN hardware platform is a network interface **202** that receives an integrated signal arriving on a high bandwidth connection **204**. Network interface **202** distributes the various components of the integrated signal to end user
25 devices or interfaces accordingly.

 There are at least four types of signals that RANs will distribute within a residence. One signal is an RJ11 twisted pair analog voice signals **206**. This is a common standard analog telephone signal. Another signal is an
30 Ethernet data signal **208** for handling packet based data

signals. A third signal is a coaxial signal **210** containing standard definition television signals. A fourth signal is a broadband broadcast signal **212** carrying high definition television signals.

5 In addition to network interface **202**, the RAN hardware platform also includes storage (memory) **214** and an applications processing engine **216**. Applications processing engine **216** includes a processor and executes resident RAN software.

10 **FIGURE 3** is a prior art illustration of OSI stack layers. OSI stands for "Open Systems Interconnection" and was developed by the International Standards Organization. OSI is a framework of standards for communication between different systems made by different vendors. The goal was
15 to create an open systems networking environment where any vendor's computer system, connected to any network, can freely share data with any other computer system on that network or a linked network. The OSI model illustrated in **FIGURE 3** organizes the communications process into seven
20 (7) different categories and places these categories in a layered sequence based on their relation to the user. Layers 7 through 4 concern end to end communications between a message source and a message destination, while layers 3 through 1 concern network access.

25 Layer 1, the physical layer, pertains to the physical means of sending data over lines (i.e., the electrical, mechanical, and functional control of data circuits). Layer 2, the data link layer, pertains to procedures and protocols for operating the communications lines. It also
30 includes means for detecting and correcting message errors.

Layer 3, the network layer, pertains to how data is transferred between computers. It also addresses routing within and between individual networks. Layer 4, the transport layer, pertains to the rules for information exchange and manages end-to-end delivery of information within and between networks, including error recovery and flow control. Layer 5, the session layer pertains to dialog management. It controls the use of the basic communications facility provided by the transport layer.

Layer 6, the presentation layer, provides transparent communication services by masking the differences of varying data formats (character codes, for instance) between dissimilar systems. Layer 7, the applications layer, pertains to functions for particular applications services, such as file transfer, remote file access, and virtual terminals.

FIGURE 4 is an illustration of OSI stack layers as applied to one embodiment of the present invention. Layers 5 and 6 play an important role in RAN architecture. As stated above, the session layer pertains to dialog management controlling the use of the basic communications facility provided by the transport layer(s) while the presentation layer provides transparent communication services by masking the differences of varying data formats between dissimilar systems. As applied to the present invention, a RAN protocol and software platform performs numerous functions at the session and presentation OSI layers. These functions include, but are not limited to, account registration, account authentication, address provisioning, firewall and other security measures, billing

services, QOS management, and subscriber network interface management. A RAN software platform is responsible for protocol and content communications on a per session basis among Customer Premises, Application Service Provider, and
5 Network Access Provider RAN platforms. To achieve its functions, RAN software utilizes an application programming interface **410** between itself and the OSI transport layers **420** and another application programming interface **430** between itself and a specific application **440**.

10 RAN functionality includes a mechanism by which each RAN identifies itself to the Network Access Provider and requests service by a mechanism in which each RAN identifies it's service capabilities, such as max/min bandwidth requirements, subscriber features supported,
15 network interfaces supported, applications in residence on the RAN, available network routes, subscriber addresses/aliases supported, and a means by which user profile information is downloaded from the Network Access Provider.

20 With respect to authenticating subscriber access, RAN protocol includes a means by which the Network Access Provider grants or denies access to each individual RAN, a means by which the Network Access Provider grants or denies services on a per use basis, and a means by which
25 Application Service Providers grant or deny services on a per use and/or user basis without intervention of the Network Access Provider.

RAN also implements a protocol for providing secure access to the Access Network. This protocol includes a
30 means by which the network and a Customer Premises RAN pass

data securely over the Access Network, and a means by which RANs pass application specific data to other RANs securely over the Access Network.

FIGURE 5 is an illustration of RAN protocol data **510** exchanges and content data **520** exchanges among a Customer Premises RAN platform, a managed packet backbone server (MPBS) RAN platform, and an Application Service Provider RAN platform. **FIGURE 5** is best described with reference to a practical example of RAN architecture in operation.

Take the case of a network subscriber using his Customer Premises RAN platform **112** that wishes to download a movie from an Application Service Provider (ASP) specializing in "movie rentals" via the ASP RAN platform **110**. There are several factors to consider in this proposed transaction. These factors, in no particular order, include, the subscriber making the download request to the ASP, the ASP verifying the identity of the subscriber, the ASP transferring the movie to the subscriber, and the ASP billing the subscriber for the movie. We now examine each part of the transaction with respect to RAN architecture.

The subscriber initially makes a request to the ASP for a particular movie. This necessarily entails the subscriber having access to the ASP system. Most likely access will be based upon methods currently in use today, e.g., a web browser interface to a web page managed by the ASP. The web page would likely list the movies available for download and provide a means for effecting a download such as clicking on an icon representing the movie. Assume the subscriber selects a movie and clicks on the "download

movie" icon or its equivalent. Clicking on the icon initiates a specialized session between the ASP RAN platform **110** and the subscriber's Customer Premises RAN platform **112**.

5 The subscriber's Customer Premises RAN platform **112** registration data is sent to the managed packet backbone server (MPBS) RAN platform **124** for authentication. Upon authentication, MPBS RAN platform **124** provides address provisioning and security between the ASP RAN platform **110**
10 and the subscriber's Customer Premises RAN platform **112** so that the subscriber, and only the subscriber, will receive the content requested from the ASP.

During registration, the MPBS RAN platform **124** receives pertinent data from the subscriber's Customer
15 Premises RAN platform **112** and the ASP RAN platform **110** and can quickly perform the above mentioned functions. The pertinent data includes each RAN identifying it's service capabilities, such as max/min bandwidth requirements, subscriber features supported, network interfaces
20 supported, applications in residence, available network routes, subscriber addresses/aliases supported, and a means by which user profile information is downloaded from the Network Access Provider.

Using the MPBS RAN platform **124** as an intermediary
25 (e.g., a service broker) between ASPs and subscribers creates a system where individual subscribers do not need to register with individual ASPs. The managed packet backbone server is responsible for matching an ASP with a subscriber on a per use basis. Thus, in the movie example
30 above, when a subscriber initiates a session with a

particular ASP, the ASP queries the MPBS with respect to the subscriber and the MPBS manages the entire transaction with the notable exception of content delivery which is between the ASP and the subscriber directly.

5 Once a secure session has been established between the subscriber and the ASP, the content **520** is ready to be downloaded over managed packet backbone **100** to the subscriber. The content of this example (multi-media data) can be very large in size. Thus, high bandwidth
10 connections facilitate such data transfers. Without a high bandwidth connection between the ASP and the subscriber, downloading a typical movie could take several hours. If a download takes too long it becomes a much less attractive alternative to subscribers.

15 MPBS RAN platform **124** provisions a direct high bandwidth connection between the ASP RAN platform **110** and the subscriber's Customer Premises RAN platform **112** complete with security measures. At this point in the session for this connection established by MPBS RAN
20 platform **124** the movie is downloaded to the subscriber over managed packet backbone **100**. Bandwidth allocation and billing can vary depending on the content involved.

 In order to make the transaction complete, the ASP, and the Network Access Provider (NAP) must be able to bill
25 for their services. The NAP owns and manages packet backbone **100**. It is their physical connections that are being used to deliver the content. There are two fundamental methods of billing in this RAN based system. One method is to bill on a flat fee basis for services.
30 The other is to bill on a per packet basis for services.

The former would charge a uniform fee based on the service requested. In the movie example, the fee could be \$ 3.50 to download a movie billed to either the subscriber or the Application Service Provider. If billed to the Application Service Provider, the Application Service Provider would then collect the fee from the subscriber. The latter method would charge a variable fee depending on the impact of the packet transfer to the NAP's infra-structure. Referring again to the movie example, a 90 minute movie without a lot of special effects can be transmitted in a lesser number of data packets than a 2 ½ hour tech laden movie. Thus, the impact to the NAP can be measured by the number and type of data packets required to achieve a task. If the number and type of data packets used to achieve a task can be determined, a variable tariff can be set. This requires the creation of packet metering algorithms.

Packet metering algorithms monitor the amount and type of data traveling between an Application Service Provider RAN platform **110** to a Customer Premises RAN platform **112**. Packet metering involves having the Customer Premises (subscriber) RAN platform **112** log and pass billing information (number and type of data packets) to the managed packet backbone server (MPBS) RAN platform **124** on a solicited or unsolicited basis once the session has terminated.

RAN billing protocol includes a means by which packet metering (billing) for raw data flows can be established and reported back to the Network Access Provider RAN platform, a means by which packet metering for data flows based on other parameters, such as time of day, content,

day of week, can be established and reported back to the Network Access Provider RAN platform, a means by which the above capabilities can be delivered between an Application Service Provider and an RAN subscriber without the intervention of the Network Access Provider, and a means by which the Network Access Provider can offer the above services to an Application Service Provider without the intervention of the subscriber.

FIGURES 6A-D illustrate RAN registration, session establishment, an actual session, and session reporting flowcharts.

FIGURE 6A illustrates the registration process that occurs when a new RAN platform goes on-line with the managed packet backbone. Registration occurs for both Customer Premises Equipment (CPE) RAN platforms and Application Service Provider (ASP) RAN platforms. When a new CPE RAN joins the managed packet backbone of the Network Access Provider (NAP), the CPE RAN sends a registration request **604a** to the managed packet backbone server (MPBS) RAN. The registration request contains a profile of the requesting CPE RAN platform. The profile includes data pertaining to the address of the CPE RAN, and the capabilities of the CPE RAN platform. Capabilities include, but are not limited to, the bandwidth that the CPE RAN can support, the network connections that the CPE RAN can support, the applications that the CPE RAN can support, any account information associated with the CPE RAN, etc. The MPBS RAN, in its capacity of a service broker, stores the profile information **606a**. The MPBS concludes the registration process by issuing an authentication key **608a**

to the requesting CPE RAN. The authentication key is used by the CPE RAN when it wishes to establish a session with another member (CPE or ASP RAN platform) of the managed packet backbone.

5 Similarly, when a new ASP RAN goes on-line, the ASP RAN sends a registration request **604b** to the managed packet backbone server (MPBS) RAN. The registration request contains a profile of the requesting ASP RAN platform. The profile includes data pertaining to the address of the ASP
10 RAN, and the capabilities and services of the ASP RAN platform. Capabilities include, but are not limited to, the bandwidth that the ASP RAN can support, the network connections that the ASP RAN can support, the applications that the ASP RAN can support, any account information
15 associated with the ASP RAN, etc. The MPBS RAN stores the ASP RAN profile information **606b**. The MPBS concludes the registration process by issuing an authentication key **608b** to the requesting ASP RAN. The authentication key is used by the ASP RAN when it wishes to establish a session with
20 another member (CPE or ASP RAN platform) of the managed packet backbone.

FIGURE 6B illustrates the session establishment process **610** between a CPE RAN and an ASP RAN. When a CPE RAN wishes to order a movie, for instance, from an ASP RAN that provides such a service, the CPE RAN first establishes
25 a session with the ASP RAN. The CPE RAN sends a session request to the MPBS RAN **612**. The session request includes details about the requested session such as the destination address (most likely in an alias form) and the amount of
30 bandwidth requested for the session. The MPBS RAN acts as

a service broker. Once it receives the session request from the CPE RAN the MPBS RAN checks for the authentication key **614** the CPE RAN was issued when it registered. The MPBS RAN then validates **616** the authentication key. If the authentication key is missing or invalid then the session establishment is terminated. An error message or other type of interrupt message may be sent to the CPE RAN explaining the reason for termination. If the authentication key is valid then the MPBS RAN determines whether the requested services can be provided **618** between the CPE and the ASP RANs. The MPBS RAN determines this by accessing the RAN profiles of the CPE and ASP in question. If the request for services can not be handled then the MPBS RAN terminates the session establishment. Again, an error message or other type of interrupt message may be sent to the CPE RAN explaining the reason for termination. Otherwise, the MPBS RAN sends a session request to the ASP RAN **620**. The ASP RAN accepts the session request **622** and sends a token associated with that specific request back to the MPBS RAN. The MPBS RAN then forwards the token **624** to the CPE RAN informing the CPE RAN that a session can be established. The CPE RAN then sends a session request **626** including the token directly to the ASP RAN. The ASP RAN validates the token **628** and denies the session request **630** if the token is invalid or accepts the session request **632** if the token is valid.

Once a session has been established, data can be exchanged **640**, as shown in **FIGURE 6C**, between the CPE RAN and the ASP RAN according to the parameters of the session request. A session initiation event message is sent **642** by

the CPE RAN to the MPBS RAN. The MPBS RAN records the commencement and termination of each session between RAN platforms on its network. The CPE RAN makes a specific request **644** of the ASP RAN. For instance, the request could be to stream a movie from the ASP database to the CPE RAN. The ASP complies with the request and streams the requested movie **646** from its database to the CPE RAN over the managed packet backbone using the bandwidth allocated by the MPBS RAN. Upon completion of the "download" a session termination event message is sent **648** from the CPE RAN to the MPBS RAN.

FIGURE 6D illustrates the session reporting process **650** that occurs upon the termination of a session between two RAN platforms. When a session has been terminated the CPE (the requesting RAN platform) reports the number and type of data packets that have been received as a result of the session. The MPBS RAN inputs the packet data into a packet metering algorithm which calculates an impact fee **654**. The impact fee is then billed out **656** to the ASP RAN and/or the CPE RAN. Alternatively the impact fee may be debited against an account corresponding to the ASP or CPE RAN and maintained by the MPBS RAN.

The flowcharts of **FIGURES 6A-D** apply to scenarios in which CPE RANs and ASP RANs communicate with one another. The same principles apply to communication between CPE RANs such as, for example, when one CPE RAN platform wishes to engage another CPE RAN platform in a computer video game.

RAN is a cost effective offering that integrates leading edge network and customer premises interfaces with a scaleable, programmable, application environment and

supporting protocol. This combination provides Network Access Providers with the opportunity to open new revenue streams by delivering value-added services to both subscribers and Application Service Providers.

5 It is to be understood that the present invention illustrated herein is readily implementable by those of ordinary skill in the art as a computer program product having a medium with a computer program embodied thereon. The computer program product is capable of being loaded and
10 executed on the appropriate computer processing device(s) in order to carry out the method or process steps described. Appropriate computer program code in combination with hardware implements many of the elements of the present invention. This computer code is often stored on
15 storage media. This media can be a diskette, hard disk, CD-ROM, optical storage media, or tape. The media can also be a memory storage device or collection of memory storage devices such as read-only memory (ROM) or random access memory (RAM). Additionally, the computer program code can
20 be transferred to the appropriate hardware over some type of data network.

The present invention has been described, in part, with reference to flowchart illustration(s) or message diagram(s). It will be understood that each block of the
25 flowchart illustration(s) or message diagram(s), and combinations of blocks in the flowchart illustration(s) or message diagram(s), can be implemented by computer program instructions.

These computer program instructions may be loaded onto
30 a general purpose computer, special purpose computer, or

other programmable data processing apparatus to produce a machine, such that the instructions which execute on the computer or other programmable data processing apparatus create means for implementing the functions specified in the flowchart block(s) or message diagram(s).

These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means which implement the function specified in the flowchart block(s). The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the flowchart block(s) or message diagram(s).

Accordingly, block(s) of flowchart illustration(s) or message diagram(s) support combinations of means for performing the specified functions, combinations of steps for performing the specified functions and program instruction means for performing the specified functions. It will also be understood that each block of flowchart illustration(s) or message diagram(s), and combinations of blocks in flowchart illustration(s), or message diagram(s) can be implemented by special purpose hardware-based computer systems that perform the specified functions or

steps, or combinations of special purpose hardware and computer instructions.

In the following claims, any means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Therefore, it is to be understood that the foregoing is illustrative of the present invention and is not to be construed as limited to the specific embodiments disclosed, and that modifications to the disclosed embodiments, as well as other embodiments, are intended to be included within the scope of the appended claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

CLAIMS:

1. A computer system for managing data exchanges among a plurality of network nodes comprising:

a managed packet backbone server (MPBS);

5 at least one Customer Premises Equipment (CPE) node communicable with the managed packet backbone server (MPBS); and

at least one Application Service Provider (ASP) node communicable with the managed packet backbone server

10 (MPBS),

wherein

the managed packet backbone server (MPBS) manages transactions among said at least one Customer Premises Equipment (CPE) node and said at least one Application
15 Service Provider (ASP) node.

2. The computer system of claim 1 wherein the at least one Customer Premises Equipment (CPE) node registers with the managed packet backbone server (MPBS).

20

3. The computer system of claim 2 wherein the at least one Application Service Provider (ASP) node registers with the managed packet backbone server (MPBS).

25

4. The computer system of claim 3 wherein the managed packet backbone server (MPBS) issues an authentication key to the at least one Customer Premises Equipment (CPE) node it registers.

5. The computer system of claim 3 wherein the managed packet backbone server (MPBS) issues an authentication key to the at least one Application Service Provider (ASP) node it registers.

5

6. The computer system of claim 4 wherein the managed packet backbone server (MPBS) stores profile information pertaining to the at least one Customer Premises Equipment (CPE) node it registers.

10

7. The computer system of claim 5 wherein the managed packet backbone server (MPBS) stores profile information pertaining to the at least one Application Service Provider (ASP) node it registers.

15

8. The computer system of claim 6 wherein a request from the at least one Customer Premises Equipment (CPE) node to establish a session with the at least one Application Service Provider (ASP) node is managed by the managed packet backbone server (MPBS).

20

9. The computer system of claim 6 wherein a request from the at least one Customer Premises Equipment (CPE) node to establish a session with another Customer Premises Equipment (CPE) node is managed by the managed packet backbone server (MPBS).

25

10. The computer system of claim 8 wherein when the managed packet backbone server (MPBS) receives a request from the at least one Customer Premises Equipment (CPE)

30

node to establish a session with the at least one Application Service Provider (ASP) node, the managed packet backbone server (MPBS):

verifies that the Customer Premises Equipment (CPE)

5 node has a valid authentication key,

sends a session request to the Application Service Provider (ASP) node,

receives a session token from the Application Service Provider (ASP) node, and

10 sends the session token to the Customer Premises Equipment (CPE) node.

11. The computer system of claim 10 wherein one of the at least one Customer Premises Equipment (CPE) nodes initiates
15 a session with one of the at least one Application Service Provider (ASP) nodes by sending a session request to one of the at least one Application Service Provider (ASP) nodes including the session token obtained from the managed packet backbone server (MPBS).

20

12. The computer system of claim 11 wherein one of the at least one Application Service Provider (ASP) nodes verifies a received session token and establishes a session with one of the at least one Customer Premises Equipment (CPE) nodes
25 if the session token is valid.

13. The computer system of claim 12 wherein one of the at least one Customer Premises Equipment (CPE) nodes sends a session initiation event message to the managed packet
30 backbone server (MPBS) upon establishment of a session with

one of the at least one Application Service Provider (ASP) nodes.

14. The computer system of claim 13 wherein one of the at least one Customer Premises Equipment (CPE) nodes sends a session termination event message to the managed packet backbone server (MPBS) upon termination of a session with one of the at least one Application Service Provider (ASP) nodes.

15. The computer system of claim 14 wherein one of the at least one Customer Premises Equipment (CPE) nodes sends data pertaining to the number and type of data packets received during a session with one of the at least one Application Service Provider (ASP) node to the managed packet backbone server (MPBS).

16. The computer system of claim 15 wherein the managed packet backbone server (MPBS) calculates a fee based on the data pertaining to the number and type of data packets exchanged in a session.

17. The computer system of claim 16 wherein the managed packet backbone server (MPBS) bills an account associated with one of the at least one Customer Premises Equipment (CPE) nodes.

18. The computer system of claim 16 wherein the managed packet backbone server (MPBS) bills an account associated

with one of the at least one the Application Service
Provider (ASP) nodes for the session.

19. A managed packet backbone server (MPBS) for managing
5 data exchanges among a plurality of network nodes
comprising:

a registration component responsive to said plurality of
network nodes, for:

receiving registration requests from the network
10 nodes;

obtaining and storing profile information
pertaining to each network node; and

providing an authentication key to each network
node,

15 a session establishment component responsive to said
plurality of network nodes, for:

receiving a session request message from a first
network node that wishes to establish a session with a
second network node, said session request message
20 including the authentication key associated with the
first network node;

verifying the validity of the authentication key
associated with the first network node;

25 sending a session request message to the second
network node;

receiving a session token from the second network
node; and

sending the session token to the first network
node, and

a session reporting component responsive to said plurality of network nodes, for:

receiving packet metering data pertaining to the amount and type of data exchanged over a managed packet backbone network during a session between two network nodes; and

calculating a fee based on the packet metering data.

20. A Customer Premises Equipment (CPE) node comprising: a registration component responsive to a server node, for:

sending a registration request to the server node; and

receiving an authentication key from the server node,

a session establishment component responsive to a server node, for:

sending a session request message to the server node, said session request message including the authentication key and the address of a network node that the Customer Premises Equipment (CPE) node wishes to establish a session with;

receiving a session token from the server node; and

sending a session request message to the network node that the Customer Premises Equipment (CPE) node wishes to establish a session with, said session request message including the session token, and a session reporting component responsive to a server node, for:

sending data to the server node pertaining to the amount and type of data exchanged over the managed packet backbone network during the session.

- 5 21. An Application Service Provider (ASP) node comprising:
a registration component responsive to a server node, for:
sending a registration request to a server node;
and
receiving an authentication key from the server
10 node, and
a session establishment component responsive to a server
node, for:
sending a session token to the server node; and
receiving a session token from a network node that
15 wishes to establish a session.
22. A Customer Premises Equipment (CPE) node comprising:
a network interface that receives and distributes an
integrated multi-media signal;
20 an applications processing engine that executes
software applications resident on said node; and
a memory that holds software applications resident on
said node and receives and stores data.
- 25 23. A Application Service Provider (ASP) node comprising:
a network interface that receives and distributes an
integrated multi-media signal;
an applications processing engine that executes
software applications resident on said node; and

a memory that holds software applications resident on said node and receives and stores data.

24. A computer program product for managing data exchanges among a plurality of network nodes, the computer program product having a medium with a computer program embodied thereon, the computer program product comprising:

computer program code for receiving registration requests from network nodes;

computer program code for obtaining and storing profile information pertaining to each network node;

computer program code for providing an authentication key to each network node;

computer program code for receiving a session request message from a first network node that wishes to establish a session with a second network node, said session request message including the first network node's authentication key;

computer program code for verifying the validity of the first network node's authentication key;

computer program code for sending a session request message to the second network node;

computer program code for receiving a session token from the second network node;

computer program code for sending the session token to the first network node;

computer program code for receiving packet metering data pertaining to the amount and type of data exchanged over a managed packet backbone network during a session between two network nodes; and

computer program code for calculating a fee using the packet metering data.

25. A computer program product for exchanging data among a plurality of network nodes, the computer program product having a medium with a computer program embodied thereon, the computer program product comprising:

computer program code for sending a registration request from a first network node to a server node; and

computer program code for receiving in the first network node an authentication key from the server node;

computer program code for sending a session request message from the first network node to the server node, said session request message including the authentication key and the address of a second network node that the first network node wishes to establish a session with;

computer program code for receiving in the first network node a session token from the server node;

computer program code for sending a session request message from the first network node to the second network node, said session request message including the session token; and

computer program code for sending, from the first network node, data to the server pertaining to the amount and type of data exchanged over the managed packet backbone network during the session.

26. A computer program product for exchanging data among a plurality of network nodes, the computer program product

having a medium with a computer program embodied thereon,
the computer program product comprising:

computer program code for sending a registration
request to a server node;

5 computer program code for receiving an authentication
key from the server node;

computer program code for sending a session token to
the server node; and

10 computer program code for receiving a session token
from a network node that wishes to establish a session.

27. A method of managing data exchanges among a plurality
of network nodes comprising:

registering network nodes;

15 maintaining profile information pertaining to the
network nodes;

providing an authentication key to the network nodes;

receiving session request messages from network nodes
that wish to establish sessions with other network nodes;

20 and

responding to session request messages from network
nodes that wish to establish sessions with other network
nodes;

25 28. The method of claim 27 further comprising:

receiving packet metering data pertaining to the
amount and type of data exchanged over a managed packet
backbone network during a session between two network
nodes; and

30 calculating a fee using the packet metering data.

29. A method of exchanging data between network nodes comprising:

5 sending a registration request to a server node; and
 receiving an authentication key from the server node;
 sending a session request message to the server node,
said session request message including the authentication
key and the address of a network node;
 receiving a session token from the server node;
10 sending a session request message, said session
request message including the session token.

30. The method of claim 29 further comprising:

15 sending data to the server node pertaining to the
amount and type of data exchanged over the managed packet
backbone network during the session.

31. A method of exchanging data between network nodes comprising:

20 sending a registration request to a server node;
 receiving an authentication key from the server node;
 sending session tokens to the server node; and
 receiving session tokens from network node seeking to
establish a session.

25 32. A computer readable data signal embodied in a
transmission medium comprising:

 a code segment comprising bandwidth information;
 a code segment comprising network interface
30 information;

a code segment comprising address information; and
a code segment comprising subscriber profile
information.

5 33. A computer readable data signal embodied in a
transmission medium comprising:

a code segment comprising information pertaining to
the number of data packets exchanged in a session between
two network nodes; and

10 a code segment comprising information pertaining to
the type of data packets exchanged in the session.

34. A residential access node (RAN) comprising:

15 a hardware platform for interfacing peripheral
equipment with a packet data network;

a software platform including a plurality of
application programming interfaces; and

a RAN protocol for managing communications among a
plurality of residential access nodes.

20

35. The residential access node of claim 34 wherein said
hardware platform comprises:

network interface means;

storage means; and

25 an applications processing engine.

36. The residential access node of claim 34 wherein said
software platform resides within said applications
processing engine and comprises:

a plurality of application programming interfaces implemented according to OSI standards.

37. The residential access node of claim 34 wherein said
5 RAN protocol manages the registration of the residential access node with a server.

38. The residential access node of claim 34 wherein said
RAN protocol manages a session establishment of one
10 residential access node with another residential access node.

39. The residential access node of claim 34 wherein said
RAN protocol manages a session reporting of one residential
15 access node with another residential access node.

ABSTRACT

A residential access node (RAN) running a RAN platform
5 **112** which includes means for interfacing a plurality of
peripheral equipment such as analog (POTS) phones **114**,
standard televisions **116**, computers **118**, IP telephones **120**,
and high definition televisions **122** to a packet data
network **100**. The Network Access Provider RAN platform **124**
10 manages sessions among Customer Premises RAN platforms **112**
and Application Service Provider RAN platforms **110** over
high bandwidth connections. The Customer Premises RAN
platform **112** also determines the number and type of data
packets entering or departing via the packet data network
15 **100**. Such an architecture allows for the efficient
transfer of services (data content) from Application
Service Providers to individual network access subscribers
by seamlessly accommodating various data types and
providing an integrated metering and billing mechanism
20 managed by the Network Access Provider.

TEL




FIG. 2




FIG. 3
PRIOR ART





FIG. 4






FIG. 6A




FIG. 6B




FIG. 6C





FIG. 6D



Please Type a plus sign (+) inside this box

+

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after initial Filing (surcharge (37 CFR 1.16(e)) required)	Attorney Docket Number	10717RNUS01U
	First Named Inventor	Kahveci, T.
	COMPLETE IF KNOWN	
	Application Number	
	Filing Date	
	Group Art Unit	
	Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A Computer System For Managing Data Exchanges Among A Plurality Of Network Nodes

the specification of which



is attached hereto
OR



was filed on (MM/DD/YYYY) , as United States Application Number or PCT International
Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 3659a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PC5T international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

DECLARATION – Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: ☐ Customer Number OR ☒ Registered practitioner(s) name/registration number listed below

Name	Registration Number	Name	Registration Number
Thomas A. Gigliotti	37,579	Eric P. Jensen	37,647
John H. Vynalek	37,254	John R. Witcher, III	39,877
J. Erik Fako	42,522	Gregory A. Stephens	41,329
Russell T. Morgan	43,815		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number 22033 OR ☐ Correspondence address below or Bar Code Label

Name			
Address			
Address			
City	State	Zip	
Country	Telephone	Fax	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])		Family Name or Surname	
Tunc M.		Kahveci	
Inventor's Signature	Date		
Residence: City	Morrisville	State	NC
Post Office Address	1437 Medalist Dr.		
Post Office Address			
City	Morrisville	State	NC
Zip	27560	Country	US

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.

+

Please Type a plus sign (+) inside this box

DECLARATION	ADDITIONAL INVENTOR(S) Supplemental Sheet Page 1 of 1
--------------------	---

Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Jason G.		Emery	
Inventor's Signature		Date	
Residence: City	Apex	State	NC
Post Office Address	1001 W. St. Julian Place		
Post Office Address			
City	Apex	State	NC
	Zip	27502	Country
			US
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Inventor's Signature		Date	
Residence: City		State	
Post Office Address			
Post Office Address			
City		State	
	Zip		Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Inventor's Signature		Date	
Residence: City		State	
Post Office Address			
Post Office Address			
City		State	
	Zip		Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Inventor's Signature		Date	
Residence: City		State	
Post Office Address			
Post Office Address			
City		State	
	Zip		Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Inventor's Signature		Date	
Residence: City		State	
Post Office Address			
Post Office Address			
City		State	
	Zip		Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Inventor's Signature		Date	
Residence: City		State	
Post Office Address			
Post Office Address			
City		State	
	Zip		Country